






SIMPLE TO INTEGRATE, HIGHLY RELIABLE, EASY TO SERVICE AND LOW COST















ORION Kiosk High reliability and low cost for the most recent in Orion TEAM. The orion version for ATMs and kiosks is available with grey, color, IR and UV image capturing capability.

Orion Kiosk is currently the most updated check reader/scanner available. The Orion Kiosk is engineered using the most innovative materials with low environmental impact.

The design of Orion Kiosk is elegant and stylish without compromising its functionality.

KEY SPECIFICATION:

- · Automatic alignment of documents
- · MICR: magnetic fonts CMC7 and E13B
- · OCR / Barcode / Barcode 2D
- Inkjet 1 Line OR Graphic Printer 6 Lines
- Up to 300 x 300 DPI
- · UV and IR technologies
- · Anti-intrusion System
- Metal detector and thickness control
- Double document control

PAPER HANDLING

Bidirectional Feed Mechanism - checks can be scanned and retained for storage or returned to customer for disposal

DOCUMENT SPECIFICATIONS

Width: 70 to 330 mm (2,76" to 12.99") Height: 52 to 106 mm (2.05" to 4.17") Weight: 60 to 120 g/sqm (0.13 to 0.26 lbs)

CODELINE READING

MICR: magnetic fonts CMC7 and E13B OCR (optional): optical fonts OCR-A, OCR-B, OCR A-B, OCR alphanumeric, E13B Barcode reading 1D/2D (optional) Additional deco capabilities (2D barcode, multiple snippets - optional)

IMAGE CAPTURE

Front and rear images in one pass (duplex) Red dropout imaging available 300x300 dpi or 200x200 dpi or 100x100 dpi Higher resolution available for 2D barcode decoding Grey and optional colour, UV and IR

IMAGE FORMAT

Bitmap, Jpeg, Tiff, G4 (B/W)

AUTOMATIC ALIGNMENT within an unbelievably small footprint your document will be safely processed and automatically aligned through its short flat path. If required the inkjet or graphic printer will endorse the back of the document before the image is captured.

ANTI INTRUSION performed by internal shutter system.

METAL DETECTOR thickness and electronic relevation of metallic parts.

INTERFACE

USB 2.0

API SOFTWARE TOOLS



Designed for Windows(XP or later version required), Linux and iOS

DIMENSIONS

Length: 245 mm (9.65") Width: 163 mm (6.42") Height: 122 mm (4.80") Weight: 2.5 kg (5.51 lbs)

COMPONENT

Antifraud feature by UV light or Infrared (optional) Watermarking feature on jpg image (optional)

REAR INKJET PRINTER (optional)

Programmable endorser, application controlled High-capacity cartridge, 1-line, 96 dpi, 1/8 inch Line of data can extend to full width of document In alternative AGP with graphical printer High-capacity cartridge, 6-lines, 300 dpi, 1/2 inch

DUTY CYCLE

Duty Cycle 3000 documents Life Cycle 2 millions documents



Seac Banche S.p.A.

Via dell'Albereto, 69 50041 Calenzano (Firenze) - ITALY

Tel: +39 055 887 07 00 Fax: +39 055 887 36 46 Email:info@seacbanche.com

