



Vision neXt™

The **Vision neXt** is our total teller automation platform helping banks transform their branches into customer-centric service centers. We've added unique features such as our patented auto-alignment mechanism and swing-open covers to the proven reliability for which Panini is known, packaged in a new, compact European design. All of this increases a bank's productivity, minimizes operator training, and eliminates the need for additional teller devices, lowering operational costs.

This Revolutionary Platform...

 Leverages the world's largest installed base and most trusted brand in distributed capture — the Panini Vision X — meeting and exceeding the quality and innovation benchmarks customers have come to expect from Panini.

 Provides rich functionality, optimized ergonomics, price/performance leadership, the industry's best total cost of ownership, and demonstrable savings, backed by Panini's world-class service and support capabilities.

 Features breakthrough innovation and versatile capabilities:

- Automatic document alignment to ensure transaction accuracy and integrity
- Multi-format document capture to fully extend investment to document and transaction automation
- Economical multi-function printer to enable a wide range of printing capabilities in one compact and cost effective device



Trust. Value. Innovation.

The Vision neXt is built on a foundation of distributed capture expertise embedded within the genetic code of Panini.

“As a payment technology innovator, we are not bound by conventional thinking, and the Panini Vision neXt is a testament to our ongoing effort to deliver breakthrough technology that exceeds the high expectations of our customers and partners.”

Michael Pratt,
CEO, Panini

Vision neXt™

State-of-the-Art Advanced Graphics Printer (AGP)

Capable of printing customer receipts, endorsements, validations and more.

Prints up to 14 lines of text and graphic images including logos and check images.

Full color, Dual-Sided ID Card Scanning

For new account creation or customer identification applications.

Advanced Auto-alignment

Virtually eliminating the need to hand jog or machine jog items, creating dramatic savings related to rework and errors.

Ergonomic design

With swing-open covers allowing complete visibility to device interior for cleaning, jam removal, and ink-cartridge replacement.

Practical and Breakthrough Innovation



Accurate MICR and Advanced Imaging

Advanced MICR reading algorithms – including optical correction for optimal decoding accuracy – and superior grayscale and color duplex scanning.

Exception Pocket

Efficiently manages foreign items, rejected transactions, and wrongly positioned items on the fly.

www.panini.com

PANINI S.p.A. (Headquarters)

via Po, 39
10124 Torino (Italy)
Phone +39.011.8176011
e-mail: info@panini.com

PANINI North America

577 Congress Park Drive
Dayton, OH 45459 (USA)
Phone +1.937.291.2195
e-mail: info@panini.com

PANINI Limitada

R. Francisco Leitão, 469 – cj 901 - Pinheiros
CEP 05414-025 São Paulo (Brazil)
Phone +55.11.31685521
e-mail: info@panini.com

Vision neXt™

Receipt Printer

	Stand-alone	Stackable
Dimensions	Height: 127 mm (5") Width: 137 mm (5.39") Length: 151 mm (5.94") Weight: 0.8 Kg (1.8 lbs)	Height: 141 mm (5.55") Width: 144 mm (5.67") Length: 235 mm (9.25") Weight: 2.4 Kg (5.3 lbs)
Weight	0.8 Kg (1.8 lbs).	
Print Method	Thermal line printing; monochrome.	
Speed	100 mm/sec; ~30 lps.	
Resolution	203 DPI.	
Cutter	Automatic, guillotine type, full or partial cut.	
Paper Roll	80 mm (width) x 60 mm (diameter).	
Print Width	72 mm.	
Interface	USB 2.0 Hi-Speed.	
Software	Microsoft Windows driver for XP, Vista, and Windows 7 & 8. OPOS driver (UPOS 1.13 compliant).	
Certifications	UL / FCC Class B. Electronics and mechanics following European RoHS and WEEE Directives.	
Power Supply	Desktop Switching Supplier. Autosensing Input from 100 to 240 Vac, 50 to 60 Hz. Output: 24 Vdc, 2.7A (65W). Meets CEC level V.	

HARDWARE OPTIONS

Inset USB Hub

Plugs into the rear side of the scanner with no footprint increase.

3 USB ports – 1 exposed and 2 internal.

Pass-through channel for power cable.

IR Capture

Infrared front image capture for security applications.



www.panini.com

PANINI S.p.A. (Headquarters)
via Po, 39
10124 Torino (Italy)
Phone +39.011.8176011
e-mail: info@panini.com

PANINI North America
577 Congress Park Drive
Dayton, OH 45459 (USA)
Phone +1.937.291.2195
e-mail: info@panini.com

PANINI Limitada
R. Francisco Leitão, 469 – cj 901 - Pinheiros
CEP 05414-025 São Paulo (Brazil)
Phone +55.11.31685521
e-mail: info@panini.com